

60mm
60mm
60mm
60mm
60mm
60mm

BASIC INFORMATION

This smart device issues a high decibel sound and flash alarm in hazardous situations. Mount to improve the performance of your smart security system. It is fully compatible with other solutions to best manage fire or burglary alarm.

1

WARNINGS & SAFETY INSTRUCTIONS

The following must be read, kept, and observed before installation:

- This device is compatible with radio TIS Zigbee hub
- This device needs to be connected to power plug
- Please keep in mind to first add the device to the gateway, and then plug it in the needed area

2

MOUNTING THE DEVICE

1 Simply plug into any power outlet.

3

CONFIGURATION

1 Download the App
Search for TIS Control & download the app

2 Set up your hub (if not already set in the application)

3 Go to Settings, and enter the default username and password

4 Go to the TIS-BEE configuration button, and follow the instructions

4

5 Add the Device
In the TIS-Bee configuration, press Add Device. Then, follow the instructions to add the device using the 2 available methods

a. Scan QR Method b. Search Method

Select whichever method you prefer, and follow the instructions on the app

5

6

60mm
60mm
60mm
60mm
60mm
60mm

TECHNICAL SPECIFICATIONS

Communication Protocol
Zigbee® 3.0 Network

Backup Battery
3-7V

Alarm Sound Level
95dB (1m away)

Product Dimensions
80mm x 32mm (plug not included)

Working voltage
100-240V AC

Operating Temperature
-10°C~50°C

9

LED BEHAVIOR

LED Status	Description
LED blinks 5 times and then stays on Solid for 3 seconds	Device successfully added
LED blinks slowly for 3 seconds (2 times per second)	Device pairing is failed
LED goes off during networking	Networking timed out. (Networking should be finished within 60 sec)

10

RESET TO FACTORY DEFAULT

1 Long press networking button for 5 seconds so the green LED starts flashing quickly

11

TROUBLESHOOTING

Problem	Possible Cause	Solution
Unable to pair	Device is not in pairing mode	Reset to factory mode
	Device is away from the hub, or there are obstacles	Bring the device closer to the hub
	Device is connected to another hub network	Reset to factory default & reconfigure

12

TIS CONTROL LIMITED

RM 1502-p9 Easey Comm Bldg 253-261
Hennessy Rd Wanchai, Hong Kong

www.tiscontrol.com

12

TIS BEE User Manual

12

Please read the user manual carefully before operation