

Whats up guys

Today I want talk about 1 side opening & 2 side opening curtain motor & accessory configuration

We have TIS M3 curtain motor ,wheel box,rail,curve pully ,weel box hook,clamping lug,tooth belt,belt jointers,wheel,rail connector & ceiling & wall mounting kits

First based on our window size: we cut the rail in this size: window size -14cm we can joint 2 or 3 rail with rail connector

After that,depending our rail size we cut tooth belt about double size of the rail +24cm

Next we mark a spot on the belt about the rail size +9 cm and add belt jointer .

Then We insert the belt in to the rail and also insert down the belt to the wheel box, then add the belt jointer to the end of my belt .becareful press it from up side notice, when half of the belt is inserted in to the rail,and you can see the belt jointer , you should connect the curve pully to the jointer,now the opposite end of belt should be inserted in to the other wheel box now add the jointer to the belt .






Next, we open this screw from the curvepully and the connect belt jointer and fix the second wheel box to the rail &then close the screw you can tighten or loosen by move w






heel box like that notice the curve pully should be loose enough that you can move it easily .






Next ,insert the wheels in to the rail from both sides & at the end, fix the clamping lug in the rail you can remove one of this pieces from curve pullys .

If you want to install one side opening curtain, you should remove one of the curve pullys, you can use ciling mount kits or wall mout kits also you have to add wheel box hook to connect the curtain to it and hide the motor & wheel box.

Hope this video is useful

	TIS M3 Curtain motor	Aluminum ally case Size 45*70*305mm	For TIS M3 Curtain use only
	Wheel box	Anti-aging POM material, maximum endure 105℃ driver	For TIS M3 use; 2pcs for each one rail
	Rail	Low resistance low noise Each rail 2 meters	Suitable for M3、M7、TIS Motors. standard length-140mm
	Pulley	To drag the hangings	Suitable for M3、M7、TIS Motors, 1pc for single track, 2pcs for double track
	Curve pulley	To drag the hangings	Suitable for M3、M7、TIS Motors, 1pc for single track, 2pcs for double track

	12mm tooth belt	Using effect will be better after oil immersion	Belt length= rail net length*2+ 48 belt teeth grid.
	Ceiling Mounting kits	Stainless steel material For ceiling rail installation	2~3 pcs for each meter of rail
	T shape Wall mounting kits	For Wall mounting	Wall installation, need to be used along with the ceiling mounting kits
	Wheels	Smooth, silent	6~8 pcs for each meter of rail
	Rail connector	For connecting rails if your curtain more than 2 meters	1pc for 1 connecting port

	12mm tooth belt	Using effect will be better after oil immersion	Belt length= rail net length*2+ 48 belt teeth grid.
	Ceiling Mounting kits	Stainless steel material For ceiling rail installation	2~3 pcs for each meter of rail
	T shape Wall mounting kits	For Wall mounting	Wall installation, need to be used along with the ceiling mounting kits
	Wheels	Smooth, silent	6~8 pcs for each meter of rail
	Rail connector	For connecting rails if your curtain more than 2 meters	1pc for 1 connecting port